

Specifications

| Model | MS2640SA |
|-------------------------------|---|
| Motor | 10 Hp (7.5 kw), 230/460v 3ph* |
| Hydraulic Pump Motor | 3 Hp (2.25 kw) |
| Hydraulic Oil Capacity | 15.6 gallons (60 liters) |
| Blade Speeds (Variable speed) | 49-295 fpm (15-90 m/min) |
| Blade Size (W x T x L) | 2.1" x .063" x 326.8" (54 x 1.6 x 8300mm) |
| Blade Tension | Hydraulic |
| Coolant | Recirculating |
| Coolant Capacity | 26 gallons (100 liters) |
| 90° Cutting Capacity | |
| Round | 26" (660mm) |
| Rectangular | 20.5" x 40" (520 x 1020mm) |
| 45° Cutting Capacity | |
| Round | 23" (620mm) |
| Rectangular | 20.5" x 24.4" (520 x 620mm) |
| 60° Cutting Capacity | |
| Round | 15.7" (400mm) |
| Rectangular | 21.3" x 15.7" (540 x 400mm) |
| Length | 148" (3750mm) |
| Width | 154" (3900mm) |
| Height | 109" (2765mm) |
| Bed Height | 31.9" (810mm) |
| Net Weight | 9,460 lbs (4300 kg) |
| Shipping Weight | 12,254 lbs (5570 kg) |

*Other voltages optional.

Design and specifications are subject to change without notice.

Clausing/Kalamazoo 26" (660mm) Semi-**Automatic Hydraulic** Swivel Head Miter Bandsaw **Features:**

- Swivel sawhead mitering from 90° to 60°
- Precision ground, oversized round column design
- 7.5 degree blade cant for longer blade life
- Heavy duty, rigid saw frame supported by two large bore hydraulic cylinders
- Cross link connecting the two columns for enhanced structural strength
- 45 degree forward & backward swivel with automatic angle lock-in smooth and powerful cutting
- Heavy duty inverter blade drive system
- Easy-to-read LED speed indicator
- Hydraulically operated carbide blade guides
- Two additional guide bearings for extra support of the blade
- Automatic hydraulic blade tensioning device
- Hydraulically actuated guide arm
- Integral coolant system
- Synchronized power driven blade brush
- Independent control station
- Precision feed pressure & feed rate dual valve system
- "Last cut" or "keep on" selector switch
- Vise pressure detector
- Hydraulically powered material infeed lift roller
- Idle roller work table for material feeding
- Light projection for precise length measurement
- Two full stroke cylinder vises
- Proximity switch for sensing blade slippage or breakage
- Electrical and hydraulic safety interlock
- Conduits protection
- Bi-metal saw blade
- Tool box, leveling pads, and an additional wire brush
- Operation & parts manual
- Two (2) year limited warranty

Accessories

- Heavy-duty Roller Table 10' x 15"
- Heavy-duty Roller Table 5' x 15"
- Stock Stand Assembly 21" 30"
- SAWZIT 1 Gallon
 SAWZIT 5 Gallon
- Hydraulic Chip Conveyor
- Variable Vise Pressure System
- Blade Deviation Detector
- Vibration Damper
 Vibration Damper
- Htomatic Wedging Resistance
- Planetary gear reducer

^{**}When machine is equipped with optional hydraulic bundle cutting attachment.