


Clausing Production Cold Saw

600 Group

*A Line of Affordable, Rugged Built,
Ferrous and Non-Ferrous Cutting
Production Circular Saws*



- Manual Cutting Machines
- Pneumatic Vise Cutting Machines
- Semi-Automatic Cutting Machines
- Automatic Cutting Machines

Clausing Kalamazoo Automatic Ferrous Cutting Circular Saw



Specifications:

Model	FHC350A
Drive Motor	2/3 Hp (2/1.5kw)
Electricals	208/230v. or 460v. - 3ph
Control	110v.
Coolant	Standard
Spindle Speeds (rpm)	70/35
Max. Blade Size	10" - 14" (250 - 350mm)
Max. Clamping Capacity	4.75" (120mm)
Feed Length Range	
Single stroke	.2" - 27.5" (5-700mm)
Double stroke	.2" - 55" (5-1400mm)
Single stroke	.2" - 82.5" (5-2100mm)
Recommended Cutting Capacity	
Round tube @ 90°	4.33" (110mm)
Square tube @ 90°	4" (100mm)
Rectangular tube @ 90°	4.33" x 2" (110 x 50mm)
Round solid @ 90°	2.36" (60mm)
Square solid @ 90°	2" (50mm)
Dimensions	
Machine Dimensions (LxWxH)	87"x48"x63" (2200x1200x1600mm)
Shipping Dimensions (LxWxH)	83"x42"x73" (2100x1050x1850mm)
Net Weight	1,984 lbs. (900kg)
Shipping Weight	2,315 lbs. (1050kg)

All specifications subject to change without notice or obligation.

Features:

- Automatic Cutting Cycle
- Automatic Feed Rate
- Auto Shut-off & Unclamping at End of Cut
- Automatic Piece Counter
- Up to 3 Cut-off Indexes for Longer Pieces
- Enclosed Worm Gear Drive for Trouble-free Operation
- 230v/460v/60/3 Electricals
- Two Speeds for Versatility
- Totally Enclosed Fan-cooled Motor
- Cast Iron Construction
- Self-centering Vise Hydraulic Double Vise
- Flood Coolant System
- Heavy Duty Sheet Metal Base
- Circular Saw Blade • Tool kit
- Operation and Maintenance Manual
- Two (2) Year Limited Warranty

Optional Equipment:

- 5 foot roller stock table
- 10 foot roller stock table
- 37" - 46" stock stand
- 1 gallon SAWZIT saw lubrication
- 5 gallon SAWZIT saw lubrication

Capacity Charts:

