



Vertical Bandsaws and Tilt Frame Bandsaws

A Line of Quality Constructed, Heavy-duty Vertical Bandsaws and Large Capacity Vertical Bandsaws



- Vertical Bandsaw with Fixed or Hydraulic Heavy-duty Cast Iron Table

Clausing Kalamazoo 12" x 20" Vertical Bandsaws

Features:

- 230v/460v/60/3 Electricals
- Magnetic Starter with 110v Control Circuit and Overload Protection
- 3 Hp (2.2Kw) TEFC Motor
- Dual Range Transmission
- 1/2" (13mm) and 3/4" (19mm) Chevron type Blade Guides with Back-Up Roller
- Fixed Table Models 26-3/4" (680mm) x 29" (736mm) Heavy-duty Cast Iron Table with two-way tilt (15°L & 45°R)
- Hydraulic Table Models 26-3/4" (680mm) x 29" (736mm) Heavy-duty Cast Iron Table with two-way tilt (15°L & 45°R) Four (4) T-Slots on Top Table Travel 13"
- Bonded Rubber Band Wheels
- 110v Work Light
- Built-in Air Chip Blower
- Blade Tension Indicator
- Blade Speed Indicator
- 3/4" (19mm) Carbon Hardback Blade
- Locking Band Wheel Doors
- Operation and Parts Manual
- Two (2) year limited warranty

Optional Equipment

- 1" Capacity Blade Welder, Shear and Flash Grinder
- Rip Fence
- Circle Cutting Attachment
- Miter Gauge
- Workholding Jaws
- 1/8", 1/4", 3/8", 1/2", 5/8", 3/4" and 1" Chevron Guide Inserts



Specifications:

Model	V2012F	V2012H
Throat	20" (508mm)	20" (508mm)
Work Height	12" (305mm)	12" (305mm)
Drive Motor	3 Hp (2.2Kw)	3 Hp (2.2Kw)
Blade Length	159"-162" (4040-4115mm)	159"-162" (4040-4115mm)
Blade Width	1/8"-1" (3-25mm)	1/8"-1" (3-25mm)
Blade Speed (fpm)	50-5200	50-5200
Dimensions		
Length	51" (1295mm)	51" (1295mm)
Width	41" (1040mm)	44" (1117mm)
Height	81" (2057mm)	81" (2057mm)
Net Weight	1,390 lbs. (630 kg)	1,500 lbs. (680 kg)
Shipping Weight	1,540 lbs. (698kg)	1,650 lbs. (748 kg)

All specifications subject to change without notice or obligation.

Clausing Kalamazoo 12" x 28" Vertical Bandsaws



Features:

- 230v/460v/60/3 Electricals
- Magnetic Starter with 110v Control Circuit and Overload Protection
- 3 Hp (2.2Kw) TEFC Motor
- Dual Range Transmission
- 1/2" (13mm) and 3/4" (19mm) Chevron type Blade Guides with Back-Up Roller
- Fixed Table Models 26-3/4" (680mm) x 29" (736mm) Heavy-duty Cast Iron Table with two-way tilt (15°L & 45°R)
- Hydraulic Table Models 26-3/4" (680mm) x 29" (736mm) Heavy-duty Cast Iron Table with two-way tilt (15°L & 45°R) Four (4) T-Slots on Top Table Travel 13"
- Bonded Rubber Band Wheels
- 110v Work Light
- Built-in Air Chip Blower
- Blade Tension Indicator
- Blade Speed Indicator
- 3/4" (19mm) Carbon Hardback Blade
- Locking Band Wheel Doors
- Operation and Parts Manual
- Two (2) year limited warranty

Specifications:

Model	V2812F	V2812H
Throat	28" (710mm)	28" (710mm)
Work Height	12" (305mm)	12" (305mm)
Drive Motor	3 Hp (2.2Kw)	3 Hp (2.2Kw)
Blade Length	197"-199" (5004-5055mm)	197"-199" (5004-5055mm)
Blade Width	1/8"-1" (3-25mm)	1/8"-1" (3-25mm)
Blade Speed (fpm)	50-5200	50-5200
Dimensions		
Length	61" (1550mm)	61" (1550mm)
Width	41" (1040mm)	44" (1117mm)
Height	91" (2311mm)	91" (2311mm)
Net Weight	1,650 lbs. (748 kg)	1,760 lbs. (798 kg)
Shipping Weight	1,800 lbs. (816kg)	1,900 lbs. (861 kg)

All specifications subject to change without notice or obligation.

Optional Equipment

- 1" Capacity Blade Welder, Shear and Flash Grinder
- Rip Fence
- Circle Cutting Attachment
- Miter Gauge
- Workholding Jaws
- 1/8", 1/4", 3/8", 1/2", 5/8", 3/4" and 1" Chevron Guide Inserts

Clausing Kalamazoo Large Capacity 14" x 40" Vertical Bandsaws

Features:

- 230/460/60/3 Electricals
- Magnetic Starter with 110V Control Circuit and Overload Protection
- 5 Hp TEFC Motor, with Brake (full stop from max. speed within 10 seconds)
- Dual Range Transmission
- 1" (25.4mm) Chevron type Blade Guides with Back-Up Roller
- 29" (737mm)W x 27" (686mm)L Heavy Duty Cast Iron Table with two-way tilt (15°L & 45°R)
- 29-1/2" (749mm)W x 27-.1/2" (699mm)L Heavy Duty Cast Iron Table with two-way tilt (15°L & 45°R) Four (4) T-Slots on Top (Hydraulic table only) Table Travel 13" (330mm)
- Auxiliary Table 19" (483mm)W x 26-3/4" (679mm)L
- Bonded Rubber Band Wheels
- 110V Work Light
- Built-in Air Chip Blower
- Blade Tension Indicator
- Blade Speed Indicator
- 1" (25.4mm) Carbon Hardback Blade
- Locking Band Wheel Doors
- Operation and Parts Manual
- Two (2) Year Limited Warranty

Optional Equipment

- 1" Capacity Blade Welder, Shear and Flash Grinder (Carbon stock only)
- Rip Fence
- Circle Cutting Attachment
- Miter Gauge
- Workholding Jaws
- 1/8", 1/4", 3/8", 1/2", 5/8", 3/4" and 1" Chevron Guide Inserts



Specifications:

Model	V4014F	V4014H
Throat	40" (1016mm)	40" (1016mm)
Work Height	14" (356mm)	14" (356mm)
Table Height	54" (1372mm)	54" (1372mm)
Drive Motor	5 Hp (3.75Kw)	5 Hp (3.75Kw)
Blade Length	260"-263" (6604-6680mm)	260"-263" (6604-6680mm)
Blade Width	1/8"-1 1/4" (3-25mm)	1/8"-1 1/4" (3-25mm)
Blade Speed (fpm)	50-5200	50-5200
Dimensions		
Length	72" (1829mm)	72" (1829mm)
Width	39" (991mm)	39" (991mm)
Height	113" (2870mm)	113" (2870mm)
Net Weight	2,976 lbs. (1350 kg)	3,395 lbs. (1540 kg)
Shipping Weight	3,395 lbs. (1540kg)	3,627 lbs. (1645 kg)

All specifications subject to change without notice or obligation.

Clausing Kalamazoo Vertical Bandsaw Accessories



Miter Gauge for Hydraulic Table Shown

Part No.	Description	Weight
KM388F	Rip Fence, Fixed Table	10 lbs.
KM388H	Rip Fence, Hydraulic Table	10 lbs.

Part No.	Description	Weight
KM198	Miter Gauge Fixed Table	30 lbs.
KM198H	Miter Gauge Hydraulic Table	7 lbs.



Part No.	Description	Weight
KM260	Circle Cutting Attachment	8 lbs.



Clausing Installed Welder, Shear, and Grinder. Welder capacity: 1" carbon Blades.

Part No.	Voltage	Weight
SM1975/H	230v	60 lbs.
SM1975/R	460v	60 lbs.



Part No.	Description	Weight
KM2002	Workholding Jaw	37 lbs.
3006080	Right Side Manual Vise (for model VG450L)	105 lbs.

Part No.	Description
KM1250	Chevron Guide Inserts 1/8" (set of 4)
KM2500	Chevron Guide Inserts 1/4" (set of 4)
KM3750	Chevron Guide Inserts 3/8" (set of 4)
KM5000	Chevron Guide Inserts 1/2" (set of 4)
KM7500	Chevron Guide Inserts 3/4" (set of 4)
KM1000	Chevron Guide Inserts 1" (set of 4)



Clausing Kalamazoo Vertical Bandsaw Material Handling

Part No.	Description	Weight
SA24T	21" x 10' (31" - 39") Heavy Duty Roller Table	485 lbs.
SA25T	21" x 5' (31" - 39") Heavy Duty Roller Table	325 lbs.
SA26T	25" x 10' (31" - 39") Heavy Duty Roller Table	500 lbs.
SA27T	25" x 5' (31" - 39") Heavy Duty Roller Table	325 lbs.



Your Single Source for Machine Tools

Clausing Precision Drills

- Clausing Belt-drive Drills
- Clausing Geared-head Drills
- Clausing Radial Drills

Clausing Precision Mills

- Clausing Bed Mills
- Clausing CNC Bed Mills
- Clausing Knee Mills
- Clausing CNC Knee Mills

Clausing Precision Lathes

- Clausing/Colchester Geared Head Lathes
- Clausing/Colchester Professional V.S. Lathes
- Clausing Large Swing Standard and CNC Lathes
- Clausing/Metosa Standard and CNC Lathes

Clausing Precision Grinders

- Clausing Manual Grinders
- Clausing 2 Axes Hydraulic Grinders
- Clausing 3 Axes Hydraulic Grinders
- Clausing ASDII & ASDIII Automatic Grinders

Clausing Precision Cutting Machines

- Clausing/Kalamazoo Horizontal Bandsaws
- Clausing/Kalamazoo Vertical Bandsaws
- Clausing/Kalamazoo Cold Saws