

Specifications

Model	MS1218VS
Drive Motor	2 Hp (1.5kw) 230/460v 3 phase
Hydraulic Motor	0.25 Hp (.19kw)
Coolant Pump	10.125 Hp (.1kw)
Band Wheel Diameter	15.4" (391mm)
Blade Size	1" x .035" x 11'-4.5" (25 x .9 x 3467mm)
Bed Height	21.75" (552mm)
Vise Opening	18" (457mm)
Blade Speeds	80-360 fpm (24-110 m/min)
90° Cutting Capacity Round Square Rectangular (H x W)	12" (305mm) 10" x 10" (254 x 254mm) 10" x 16" (254 x 406mm)
45° Cutting Capacity Round Square Rectangular (H x W)	8" (203mm) 8" x 8" (203 x 203mm) 8" x 12" (203 x 305mm)
Length	75" (1905mm)
Width/with stock stop	34"/49.5" (864/1257)mm)
Height (head-up)	64" (1626mm)
Height (head-down)	41" (1041mm)
Net Weight	926 lbs. (420kg)
Shipping Weight	1129 lbs. (512mm)
Shipping Dim. (LxWxH)	78" x 36" x 46" (1981mm x 914mm x 1168mm)

All specifications subject to change without notice or obligation.

CLAUSING 12" (305MM) WET CUTTING SEMI-AUTOMATIC MITER BANDSAW

Features


- 0°-45° Miter cutting, make angle cuts without swinging material to be cut
- 2 Hp (1.5kw) main drive motor with magnetic starter and overload protection
- Infinity variable speed drive
- 230/460v 60 cycle 3 phase electricals
- Recirculating coolant system with application through both guides
- Solid carbide blade guides with rollers
- Quick action vise
- · Automatic shut-off at end of cut
- Totally enclosed transmission
- Blade cleaning brush
- · Cast iron bed
- 1" (254mm) wide blade
- Stock stop
- Easily adjusted head feed with hydraulic power head lift
- Two (2) year limited warranty

Accessories

- P10 Stock Stand Assembly 21"-30"
- SA12 Roller Table Assembly 10' x 18"
- SA13 Roller Table Assembly 5' x 18"
- BT01 Bandsaw Blade Tension Gauge
- CSR1 SAWZIT 1 Gallon
- CSR5 SAWZIT 5 Gallon

Cutting Capacities

Capacity at 90°



Capacity at 45°

