

MANUAL BANDSAW



Specifications

Model	MS9	MS9S1	MS10D
Туре	Horizontal Miter	Horizontal Miter	Horizontal Double Miter
Motor	1.5 Hp 3 phase	1.5Hp 1 phase	2 Speed 1.5 Hp 3 Phase
Step Speed Drive	2	Single Pulley	_
Variable Speed	_	_	Yes
Blade Size	1" x .035" x 96.5"	1" x .035" x 96.5"	1" x .035" x 120.3"
Blade Speeds Step	132 and 264 FPM	264 FPM	118-236 FPM
Blade Speeds Variable	_	_	
90° Cutting Capacity Round Rectangular (H x W)	8.9" (225mm) 9.45" x 6" (240 x 150mm)	8.9" (225mm) 9.45" x 6" (240 x 150mm)	10.2" (260mm) 13.8" x 7.9" (350 x 200mm)
45° Cutting Capacity + Round Rectangular (H x W)	5.75" (145mm) 5.75" x 8.27" (145 x 210mm)	5.75" (145mm) 5.75" x 8.27" (145 x 210mm)	7.9" (200mm) 8.7" x 7.9" (220 x 200mm)
45° Cutting Capacity - Round Rectangular (H x W)			7.9" (200mm) 9.1" x 7.9" (230 x 200mm)
60° Cutting Capacity + Round Rectangular (H x W)	3.5" (90mm) 3.5" x 7" (90 x 180mm)	3.5" (90mm) 3.5" x 7" (90 x 180mm)	5.5" (140mm) 5.5" x 5.5" (140 x 140mm)
Bed Height from Floor	39.5"	39.5"	39.5"
Width	53" (1350mm)	53" (1350mm)	63.4" (1610mm)
Depth	28" (715mm)	28" (715mm)	39.4" (1000mm)
Height (head down)	52.2" (1326mm)	52.2" (1326mm)	64.5" (1639mm)
Net Weight	550 lbs. (250kg)	550 lbs. (250kg)	792 lbs. (360kg)
Shipping Weight	620 lbs. (281kg)	620 lbs. (281kg)	900 lbs. (409kg)
Shipping Dim. (L x W x H)	60" x 35" x 60"	60" x 35" x 60"	70" x 45" x 71"

All specifications subject to change without notice or obligation.

CLAUSING KALAMAZOO 9" AND 10" WET CUTTING SWIVEL BANDSAWS

Features

- 1.5 Hp drive motor, heavy duty reducer and step pulley drive MS9 and MS9S1
- 1.5 Hp drive motor, heavy duty reducer and variable Speed drive MS10D
- Swivel angle 0–60 degree left MS9 and MS9S1
- Double swivel for adjustable left or right angles MS10D
- Feed down cyclinder
- Motor with worm gear driven gear box with hardened and ground worm shaft MS9 and MS9S1
- 2-Speed motor with worm gear driven gear box with hardened and ground worm shaft MS10D
- · Bi-Metal saw blade
- Blade tension gauge system
- Coolant system
- Machine stand with door
- Operation and parts manual
- Two year limited warranty
- Voltages are 220v/1ph for MS9S1
- Voltages are 230v/3 phase for MS9 and MS10D all other voltages may require a transformer or special order