

- Manual Cutting Machines
- Pneumatic Vise Cutting Machines
- Semi-Automatic Cutting Machines
- Automatic Cutting Machines



www.KalamazooSaws.com info@KalamazooSaws.com 800-575-2843 714-846-2700 Clausing Kalamazoo Automatic Non-Ferrous Cutting Circular



Specifications:

Model	FHC350NA
Drive Motor	5 Hp (3.7kw)
Electricals	208/230v. or 460v 3ph
Control	110v.
Coolant	Standard
Spindle Speeds (rpm)	3200
Max. Blade Size	14" (350mm)
Max. Clamping Capacity	5.9" (150mm)
Feed Length Range	
Single stroke	.2" - 27.5" (5-700mm)
Double stroke	.2" - 55" (5-1400mm)
Single stroke	.2" - 82.5" (5-2100mm)
Recommended Cutting Capacity	
Round tube @ 90°	4.33" (110mm)
Square tube @ 90°	4.33" (110mm)
Rectangular tube @ 90°	4.33" x 3.5" (110 x 90mm)
Round solid @ 90°	3.5" (90mm)
Square solid @ 90°	3" (75mm)
Dimensions	
Machine Dimensions (LxWxH)	87"x55"x63" (2200x1400x1600mm)
Shipping Dimensions (LxWxH)	83"x42"x73" (2100x1050x1850mm)
Net Weight	1,984 lbs. (900kg)
Shipping Weight	2,205 lbs. (1000kg)

All specifications subject to change without notice or obligation.

Features:

- Automatic Cutting Cycle
- Automatic Feed Rate
- Auto Shut-off & Unclamping at End of Cut
- Automatic Piece Counter
- Up to 3 Cut-off Indexes for Longer Pieces
- Enclosed Worm Gear Drive for Trouble-free Operation
- 230v/460v/60/3 Electricals
- Totally Enclosed Fan-cooled Motor
- Cast Iron Construction
- Self-centering Vise Hydraulic Double Vise
- Flood Coolant System
- Heavy Duty Sheet Metal Base
- Circular Saw Slade Tool Sit
- Operation and Maintenance Manual
- Two (2) year Limited Warranty

Optional Equipment:

- 5 foot roller stock table
- 10 foot roller stock table
- 37" 46" stock stand
- Chain chip conveyor
- 1 gallon SAWZIT saw lubrication
- 5 gallon SAWZIT saw lubrication

Capacity Charts:



